

PSS-22010/24010

2U server based on dual Intel® Xeon® E5 v4 series with up to 256GB DDR4 ECC support, VGA, GbE Ethernet and 3Gbps SATA



FEATURES

- Dual Intel® Xeon® E5 v4 series
- Support up to 256GB DDR4-2133 ECC DIMM or 512GB DDR4-1600 ECC DIMM
- IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
- 2x RJ45 Gigabit Ethernet LAN
- 4x PCIe x8
- 2x rear USB 3.0

GENERAL

Processor	<ul style="list-style-type: none">• Dual Intel® Xeon® E5 v4 series• Up to 22 cores• Up to 145W TDP
Chipset	<ul style="list-style-type: none">• Intel® C612 chipset
Memory	<ul style="list-style-type: none">• 16 slots DDR4 ECC memory<ul style="list-style-type: none">○ Support 2133 MHz, 8 DIMMs, up to 256GB○ Support 1600 MHz, 16 DIMMs, up to 512GB• RDIMM: 32GB, 16GB, 8GB, 4GB
BIOS	<ul style="list-style-type: none">• 64Mb SPI Flash EEPROM with AMI BIOS• DMI 2.3, ACPI 1.0/2.0/3.0, Plug & Play (PnP)
IPMI	<ul style="list-style-type: none">• IPMI 2.0 with virtual media over LAN and KVM-over-LAN support• ASPEED AST2400 BMC• RJ45 dedicated IPMI port
System Health Monitoring	<ul style="list-style-type: none">• System health monitoring• Onboard voltage monitors for +1.05V, 1.5V, +3.3V, 3.3VSB, +5V, +5V standby, +12V, chipset, memory, CPU1/CPU2 Vcore, and battery voltage• Low-noise fan speed control
Storage Device	<ul style="list-style-type: none">• 1x slim CD-ROM/DVD-ROM• 2x dedicated SATA III 7-pin SATA interfaces• 8x 3.5" SATA III (up to 10)• Software SATA RAID: 0/1/5/10

I/O INTERFACE

Ethernet	<ul style="list-style-type: none">• Intel® Ethernet Controller XL710• COB-G900: 2x RJ45 Gigabit Ethernet LAN (LAN one for backup IPMI port)• COB-G901: 4x RJ45 Gigabit Ethernet LAN (LAN one for backup IPMI port)
PCIe Expansion	<ul style="list-style-type: none">• 4x PCIe x8
Video	<ul style="list-style-type: none">• ASPEED AST2400 BMC• DisplayPort/VGA
USB	<ul style="list-style-type: none">• 1x front USB 2.0• 2x rear USB 3.0

Mechanical & Environment

Dimension	2U, 19"(W) x 17.7"(D) x 3.5"(H)
Power Supply	<ul style="list-style-type: none">• 800W redundant power supply• AC input: 100~240V full range• DC output: 12V/65A, -12V/0-0.8A, +5VSB/0-3.5A
Operating Environment	<ul style="list-style-type: none">• 10°C~40°C• 8~90% non-condensing
Storage Environment	<ul style="list-style-type: none">• -20°C~70°C• 5~95% non-condensing
Certification	RoHS, UL compliance



www.portwell.com

Contact PM-COMM@portwell.com to discuss your design options.